

MESH ceiling

Design Francisco Gomez Paz, 2017

**LUCE
PLAN**

Type: Ceiling


Light source: LED 50W 2700K 3.518 lm EEL: A
Dimmable phase cut

Product use: Indoor

Materials: Structure in steel, lenses in polycarbonate

Colors: Black

Description: The particular structure permits exceptional freedom in the control of luminance: it is possible to govern the intensity of the light.

Insulation class: 

Reference code: Structure
D86PLN 1D860PLN0001 black



DIMMER LIST for dimmable phase cut version

Brand	Model number (Dimmer)	Dimming Range	Leading/Trailing edge
ELKO	315GLE	7-100%	Trailing edge
Schneider	SBD315RC	10-100%	Trailing edge
Lutron	RISU-452	8-100%	Trailing edge
Lutron	LLSI-502	15-100%	Leading edge
CLIPSAL	32E450TM	15-100%	Trailing edge
CLIPSAL	32E450LM	18-100%	Leading edge
JUNG	243EX	18-100%	Trailing edge
BerKer	2875	0-100%	Leading edge
Asialink	8082	17-100%	Leading edge
DOYLE & TRATT PRODUCTS LTD	P500	17-100%	Leading edge
SIEMENS	400W	30-100%	Leading edge
VADSBO	LD220	1-100%	Trailing edge
MALMBERGS	HD2200	10-100%	Trailing edge
Eltako	EUD61NPN-UC	0-100%	Trailing edge
Eltako	EUD12NPN-UC	0-100%	Trailing edge

D86PLN
weight 3,7 Kg

